

WORKIO®

KV-S3065CL / KV-S3065CW

Robust



- Color Duplex Scanner
- Straight Pass, Long Paper Scanning
- 65 ppm / 120 ipm (200 dpi, letter)
- Ultrasonic Double Feed Detection

Panasonic ideas for life



The KV-S3065C series of high speed color scanners incorporate exceptional features and performance into a powerful, robust scanning solution.



Automatic Binary / Color distinction allows the scanner to automatically recognize color and black & white pages. An intelligent feature found on much more expensive scanners, this attribute reduces scan-to-file size while promoting a more efficient scanning process.

Switchable Reference accommodates software and driver-specific requirements by supporting both black and white references. Utilizing either a black or white reference helps to ensure the highest level of accuracy when cropping and/or de-skewing.

Hybrid Contact Image Sensor Technology, incorporating a 3-line CCD image sensor and dual fluorescent white lamps, resulting in the best of both technologies in one state-of-the-art device.



With its easy to use "clam-shell" design and stainless steel construction, the KV-S3065C Series is built to last while providing easy access for routine cleaning and maintenance. It's no wonder that the KV-S3065C Series has a duty cycle of up to 10,000 pages a day.



Accurate automatic color cropping and de-skewing has never been easier. With a flick of a lever the KV-S3065C Series easily switches to black or white reference to accommodate varying software and driver requirements, without the need to replace rollers.



Designed to increase productivity and reduce downtime, the KV-S3065C Series incorporates long lasting, easy to replace rollers. No more waiting for a service technician to perform routine roller replacements - these rollers can be replaced in seconds without any tools.

Specifications

			KV-S3065CL	KV-S3065CW
Scanning face			Duplex, Sheet Feed Scanning	
Scanning Method			Hybrid Contact Image Sensor Technology (Front and Back) Incorporating 3-Line CCD image sensor and dual fluorescent white lamps Selectable black and white background reference	
Scanning Speed <i>Letter size, portrait</i>	Binary 200 dpi		Up to 65 ppm / 120 ipm	
	Color 200 dpi		Up to 65 ppm / 120 ipm	
Resolution (Color and B/W)			600 dpi Optical Resolution 100 - 600 dpi (1 dpi step)	
Detection			Ultrasonic double-feed detection	
Image Compression	Binary		MH (G3), MR, MMR (G4)	
	Grayscale and Color		JPEG	
Image Output			Binary (simple binary, Halftone mode), Grayscale (8-bit), Color (24-bit): RGB SRBG ICC profile (TWIN), MultiStream® output	
Binary Mode Halftone			Dither, Error diffusion	
Image Control <i>Executed by driver software or Panasonic RTIV™</i>			Image Emphasis (5 steps), Gamma Correction, Dynamic Threshold, Automatic Separation, Noise Reduction, Shadow Removal, Automatic De-skewing, Automatic Cropping, Mirror Image, Monochrome Reversing, Automatic Binary / Color Detection, Automatic Multi Color Dropout and much more	
Other functions			Length Control, Detect Page Size, Detect double feed, Barcode detection (ISIS), Patch code detection, Separation sheet, Control sheet	
Paper	Size (ADF)	Minimum	1.9" width x 2.75" length	
		Maximum	8.9" width x 14"	11.9" x 17"
	Weight	Single	5.3 ~ 42 lbs (20 ~ 157 g/m ²)	
		Continuous	10.6 ~ 42 lbs (440 ~ 157 g/m ²)	
	Thickness	Single	1.0 ~ 7.9 mils (0.025 ~ 0.2 mm)	
Continuous		2.0 ~ 7.9 mils (0.05 ~ 0.2 mm)		
Automatic Document Feeder			Up to 300 sheets (17lb - 64g/m ²)	
Long Paper Mode			Up to 183.4 feet (letter size, 200 dpi)	
Interface			High-Speed USB 2.0 / Ultra SCSI (SCSI III) - 20 MB/sec	
Power Requirement			AC 100 - 200 V, 50/60 Hz (UL / CSA) AC 220 - 240 V, 50/60 Hz (CE / TUV)	
Power Consumption	Scanning		1.4 A (100~120V) / 0.6A (220~240V)	
	Standby		0.6 A (100~120V) / 0.3A (220~240V)	
	Sleep		8 Watts	
Operating Environment	Temperature		59° F to 86° F (15° C to 30° C)	
	Humidity		20%RH to 80%RH	
Storage Environment	Temperature		32o F to 95 F (0° C to 35° C)	
	Humidity		10%RH to 80%RH	
External Dimensions			19.5" (W) x 22.6" (D) x 11.3" (H) 495 mm (W) x 575 mm (D) x 288 mm (H)	
Weight			53 lbs (24 Kg)	
Accessories			CD ROM: Operation manual, Installation manual, Maintenance manual, RTIV™ manual, PIE manual, User Utility manual, control data sheet, RTIV™ capture software, ISIS® / TWAIN driver software, User Utility software Power cord, USB cable & Blower	
Options	Roller exchange kit		KV-SS017	
	Roller exchange kit (Thin Paper)		KV-SS018	
	Roller cleaning paper		KV-SS03	
	Imprinter unit (Pre and/or Post)		KV-SS014	
	Ink cartridge		KV-SS021	

As an ENERGY STAR® Partner, Panasonic has determined that this product meets the ENERGY STAR® Guidelines for energy efficiency. (ENERGY STAR® and the ENERGY STAR® certification marks are registered U.S. marks.) WORKIO® and RTIV™ are trademarks of Matsushita Electric Industrial Co., Ltd. MultiStream®, ISIS® and ISIS-Certified™ are trademarks of Pixel translations, a division of Captiva Software Corporation. All other brand or product names are the property of their respective holders. Design and specifications are subject to change without notice.



Panasonic®

Panasonic Digital Document Company, Unit Company of Panasonic Corporation of North America
Two Panasonic Way, Secaucus, NJ 07094
Call 1-800-742-8086 for a local dealer
panasonic.com/scanners

SCAN-KV-S3065C-02/04